

# Commercial LED T8/T5 Tube



Lighting Source

## Model : LT-I0609-T5G5/LT-I1218-T5G5 LT-I1522-T5G5

### Features:

1. Uniform light emission
2. High luminous output (150lm/W) & low power consumption
3. SPM Design – power circuit protection to cut off individual LEDs when mal-functioned
4. T8 body to maximize lighting effect



Model:LT-I0609-T5G5  
LT-I1218-T5G5  
LT-I1522-T5G5  
(-N series)

### Standard

Tube Dimension       $\varnothing 26.5\text{mm} \times 548/1148/1448\text{mm}$

Voltage (V)            AC85~265V

Lamp Holder            G5

Beam Angle            180 degree

CRI                        >80Ra

Luminous Efficacy    150 lm/W

Power Factor            > 0.90

Power Efficiency        90%

Power (W)

Model:  
LT-I0609-T5G5

Output power    8.1W  
Gear loss        0.9W  
Input power      9W

Model:  
LT-I1218-T5G5

Output power    16.2W  
Gear loss        1.8W  
Input power      18W

Model:  
LT-I1522-T5G5

Output power    19.8W  
Gear loss        2.2W  
Input power      22W

Lumen(lm)

Model:  
LT-I0609-T5G5

9W / 150lm/W / Total 1350lm

Model:  
LT-I1218-T5G5

18W / 150lm/W / Total 2700lm

Model:  
LT-I1522-T5G5

22W / 150lm/W / Total 3300lm

Cover Material        Aluminium , PC Cover

Color Temperature    2700K/3000K/4000K/6000K

Life Time                50,000(H)

EMC                      EN55015:2013 EN61547:2009  
EN61000-3-2:2006+A1:2009+A2:2009  
EN61000-3-3:2013

LVD                        EN60598-2-1:1989  
EN60598-1:2008+A11:2009

